



BERGER 303 Flat Emulsion

Product Description

Berger 303 Flat Emulsion is a premium quality wall paint with a smooth, flat finish. Specially formulated for the Tropical climate, Berger 303 is a low odour, low VOC, pure acrylic emulsion, with excellent durability, fungal and alkali resistance. Berger 303 will give years of beauty and protection on exterior and interior surfaces.

Design Use

Areas of use: Interior and Exterior
Substrate: Brickwork, concrete, cement rendering, gypsum, masonry and drywall.

Physical Data

Finish: Smooth
Colour: Classic colour chart; the Berger Colour World (CW) range.
Spread Rate: 10.5m²/L (White) and up to 14.0 m²/L for some colours.
Practical coverage depends on the porosity and texture of the surface. Some colours may require a primer.
Drying Time: Touch: 15 minutes; Re-coat: 1 hour.
Gloss Level: Flat

Application Data

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Use up to 250 mls clean water per 3.8L, for thinning if necessary for ease of a application.

Brush or Roller: Apply an even coat taking care to avoid runs and sags.
Spray: Use conventional spray equipment.

Additional Information

Thinner: Clean water
Storage: Store in a cool, shaded, dry area.
Hazard Rating: Non-flammable; non-toxic and lead-free
Shelf Life: 2 years
Pack Size: 0.95L, 3.8L, 19L

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

CONCRETE, PLASTER, MASONRY

New Surfaces

Smooth new surfaces, removing any loose sand, mortar splashes manually or mechanically. Prime new surfaces with one coat of Berger Alkali Sealer after it has been allowed to weather for a minimum of 30 days.

Berger Concrete Primer may also be used as an alternative primer on new concrete surfaces, which have been weathered at least 45 days.

Previously Painted Surfaces

Ensure surface is clean, dry and free from dust, grease, algae, dirt and all other contaminants. Treat fungal growth, by scrubbing or power washing with a 10% bleach solution. Rinse thoroughly and allow to dry. Apply one coat of Berger Biocidal or Sterilizing Solution ensuring that there is adequate daylight remaining for drying. Do not apply if the weather is rainy.

Surfaces showing cracking, peeling, chalking or efflorescence should be wire brushed, scraped and sanded to remove loose flaking material, and reduce previous film to a flat finish. Thoroughly dust down the entire surface; then apply one coat of Berger Alkali Sealer.

To achieve a very smooth Interior surface, apply one or two coats of Berger Interior Joint Compound; for uniform Exterior surface – use Berger Exterior Joint Compound or Berger Ready-to-Use All Purpose crack-filler to fill holes, cracks and imperfections. Sand mechanically or manually to a smooth, clean surface, removing all dust and loose particles.

WOOD

New surfaces

Sand new surfaces to a smooth finish. Prime lightly coloured wood with Berger Wood Primer and dark wood with Berger Alkali Sealer. Allow recommended time for drying.

Previously Painted Surfaces

Ensure that dirt, stains, loose material and contaminants, etc. are removed. If the surface is cracking or peeling, remove the loose material by scraping. Thoroughly dust to ensure a clean surface. Treat any fungal growth with Berger Sterilizing Solution. Apply one coat of Berger White Wood Primer, Berger Grip & Seal, Berger Alkali Sealer or Berger Luxatex Primer, allowing recommended time for drying.

GYPSUM

Sand to a smooth finish and remove all dust. Apply one coat of Berger Alkali Sealer or Berger Luxatex Primer to seal surface, allowing recommended time for drying.

METAL SURFACES

IRON AND STEEL – should be thoroughly cleaned to remove all oil, grease, rust, scale, moisture. Prime with Berger Metal Primer (Red Oxide)

ALUMINIUM & ZINC – should be degreased and etched with Berger Self Etch Primer
Contact Berger Technical Service Department for other specific recommendations.

Health & Safety

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally. Liquid paint and vapours may cause irritation. Use only with adequate ventilation. To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

First Aid

- Ingestion: Do not induce vomiting. Get medical attention immediately.
- Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
- Eye Contact: Flush immediately with water for at least 15 minutes.
- Skin Contact: Wash thoroughly with soap and water.

Recommended paint solution for painting new, cured concrete or plaster Step 1

For priming new, cured, concrete surface



Use
Berger Concrete Primer
 for dark colours

For priming wall close to or by the sea



Apply 1 coat of
Berger Alkali Sealer

For priming new wood or metal surface



For metal apply 1 coat of
Berger Red Oxide primer
 and for wood apply 1 coat of
Berger Wood Primer

Step 2



Apply 2 coats of **Berger 303 Flat Emulsion**
 Available in thousands of colours through Berger Colour World Advanced Tinting System.

Contact Us



Berger Paints Jamaica Ltd.
 256 Spanish Town Road,
 P.O. Box 8, Kingston 11, Jamaica
 Tel: +1-876-923-6226
 Fax: +1-876-923-5129
 Email: bergerja_marketing@bergeronline.com

www.bergercaribbean.com

facebook.com/BergerCaribbean

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.