



## Product Description

Berger Weather-Proof Ultra is a premium quality 100% acrylic exterior paint, specially formulated to provide a long lasting, durable finish, resistant to the most severe tropical weather. Berger WeatherProof provides a tough, weather-resistant, decorative finish on concrete, cement board, masonry and properly prepared wooden surfaces. It offers superior resistance to moisture, fungus and algae and when used according to the recommended application, qualifies for Berger's seven-year warranty. Excellent for commercial and residential applications.

## Design Use

Areas of use: Exterior  
Substrate: Concrete, plaster, masonry and gypsum.

## Physical Data

Finishes: Smooth  
Colour: White & Colour-World Tint System in Weather Proof (All) file  
Spread Rate: 12 m<sup>2</sup>/ L; 45.5 m<sup>2</sup>/3.8L (White). Spreading rate for the colours vary. Some colours require a primer; this is indicated on the Colour World chart.  
Drying Time: Touch - 15 minutes  
Recoat - 1 hour  
Gloss levels: Low sheen

## Application Data

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely.  
Use 0-6 % clean water for ease of application if required.

Brush or Roller: Apply an even coat taking care to avoid runs and sags.  
Spray: Use conventional spray equipment.

## Additional Information

Thinner: Clean water  
Storage Instruction: Store in a cool, shaded, dry area.  
Flash point: Not Applicable  
Shelf Life: 2 years  
Pack Size: 0.95Litre, /3.8Litre,/19Litre

## Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

### Concrete, Plaster, Masonry

Ensure surface is clean, dry and free from dust, grease, algae, dirt and all other contaminants. Surface must be sound and free from efflorescence. Remove efflorescence and algae by wire brush or sweep blast.

### Exterior

Prime new surfaces with one coat of Berger Alkali Sealer after it has been allowed to cure or dry for a minimum of 30 days. Apply at least 2 coats of Berger Weather-Proof Ultra. Berger Concrete Primer may also be used as an alternative primer on new concrete surfaces which have been allowed to cure or dry for at least 45 days.

If the surface is previously painted, ensure that dirt, stains, etc. and other loose material and contaminants are removed. If the surface is cracking, peeling or chalking, remove the loose material by wire brush and scraping. Thoroughly dust down the entire surface. Prime with Berger Alkali Sealer. Treat algal growth, if any, with Berger Biocidal Solution.

To achieve a uniform surface, apply Berger Surface Compound (for exterior use) to fill holes, cracks and imperfections. Smooth surface with sand paper and dust down to remove all loose particles. Apply at least two coats of Berger Weather-Proof Ultra.

Contact Berger Technical Service Department for other specific recommendations.



# BERGER Weatherproof Ultra

## Health & Safety

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air.

Avoid contact with skin or eyes.

## First Aid

Ingestion: Do not induce vomiting. Get medical attention immediately

Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

Eye Contact: Flush immediately with water for at least 15 minutes.

Skin Contact: Wash thoroughly with soap and water.

## Recommended paint solutions

### Step 1

#### For priming wall



Apply 1 coat of **Berger A.L.D. Concrete Primer** to cured, concrete, plaster or masonry surface

#### For priming alkali-prone wall



Apply 1 coat of **BERGER Alkali Sealer**

#### For priming wood



Apply 1 coat of **Berger Grip & Seal** to new wood

**Tinting recommended** for application under dark colours.

### Step 2



Apply 2 coats of **Berger Weatherproof Ultra**

## Contact Us



**Berger Paints Trinidad Ltd.**  
P.O. Box 546, 11 Concessions Road,  
Sea Lots, Port Of Spain, Trinidad  
Tel: +1-868-623-2231  
Fax: +1-868-623-1682

[www.bergercaribbean.com](http://www.bergercaribbean.com)

[facebook.com/BergerCaribbean](https://facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

