



Product Description

A high quality varnish specially formulated to give excellent mar and abrasion resistance. For use on floors and interior surfaces. Will not leave marks if cold or hot containers are placed on surface. Available in Gloss finish.

Areas of Use

Woodcare Polyurethane Varnish is ideal for all types of interior applications - Wooden Floors, Ceilings, Furniture, Doors, Stairs, Banisters, Panelling, Trim and all hard use areas.

Application

Apply liberally with a clean brush or spray. On bare wood, thin the first coat with 500mL of Berger No. 2 Reducer to 3.8L of varnish. Apply a light first coat then sand lightly. Apply second and third coats of unthinned varnish, sanding lightly between coats.

Spreading Rate:	9.6m ² per litre on normal wooden surfaces.
Drying:	Touch: 30 minutes. Recoat: 4 hours
Thinning/Clean up:	Berger No. 2 Reducer
Pack Sizes:	3.8 litre, 0.95 litre
Colour Range:	Clear
Flash Point:	36.7°C (98°F)
Pot Life:	Not applicable
Finish:	High Gloss

Surface Preparation

NEW WOOD - Should be thoroughly dry and well seasoned. Rub down thoroughly with a fine sandpaper and remove dust and debris. Staining with Berger Naptha Wood Stain may then be carried out if desired.

PREVIOUSLY VARNISHED SURFACES - if in good condition, should be thoroughly cleaned and rubbed down.

PREVIOUSLY VARNISHED SURFACES IN POOR CONDITION - Remove all old coatings with Berger Paint and Varnish Remover and treat as for new wood.

Health & Safety

Keep out of the reach of children. Wear adequate protective gear, including gloves and appropriate solvent mask. Contains petroleum distillates. Keep away from ignition sources (heat, sparks or open flame). Ensure adequate ventilation to prevent build-up of vapours during application and drying. Intentional mis-use by deliberately concentrating and inhaling contents may be harmful. **DO NOT TAKE INTERNALLY.** Avoid contact with eyes, skin and clothing. Can cause irritation.

Ingestion:	DO NOT INDUCE VOMITING. Seek medical attention immediately.
Inhalation:	If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
Eye Contact:	Flush immediately with water for at least 15 minutes.
Skin Contact:	Wash thoroughly with soap and water.

Contact Us



Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

www.bergercaribbean.com

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.



REF-WCPGV-11/2015

BERGER
WOODCARE Polyurethane Varnish (Gloss)