



## Product Description

**Berger Woodcare Marine Spar Varnish** is an alkyd modified, chlorinated rubber-based varnish, specially formulated to give a warm, amber tone and bring out the natural beauty of wooden surfaces, with a finish that performs even in the harshest conditions.

**Berger Woodcare Marine Spar Varnish** is a tough, flexible, long lasting coating made to provide protection against sun, weather, sea spray and mildew. **Berger Woodcare Marine Spar Varnish** is easy to apply and re-apply over old varnish in reasonably good condition.

## Areas of Use

**Berger Woodcare Marine Spar Varnish** gives a traditional high gloss finish to marine vessels. It is also suited for the exterior of Windows, Doors and Frames and Wooden Garden Furniture that face the onslaught of sun and rain 24 hours a day.

## Surface Preparation

Surface must be clean, dry, smooth and free from dirt, grease wax and old paint. New wood should be thoroughly dry. Previously varnished surfaces in poor condition should be thoroughly stripped Rub down to a smooth surface with fine sandpaper.

## Before Use

Always stir **Berger Woodcare Marine Spar Varnish** thoroughly.

## Application

Apply liberally with a clean brush or spray. 2 coats should be applied on varnished wood if surface is sound or 3 to 4 coats on new wood. After application, **Berger Woodcare Marine Spar Varnish** will be 'touch dry' in 4 hours. Additional coats should only be applied after a drying time of 12 hours.

## Thinning / Clean up

Clean equipment immediately with **Berger No. 3 Reducer**. Store in a cool place. Keep away from children.

## Spreading Rate

9.0-9.5 sq. metres per litre, 375-400 sq. ft / Gallon, depending on the porosity and texture of the surface.

## Drying Time

**Touch Dry:** 2 Hours.

**Recoat:** 12 Hours.

**Hard Dry:** 24 Hours.

## Pack Sizes

4 litre, 1 litre | U.S. Gallon, 1 Quart.

## Colour Range

Clear

## Packaging

4 Litre

BERGER  
Woodcare Marine Spar Varnish

#### Flash Point

37°C (98°F)

#### Pot Life

Not applicable

#### Health & Safety

**KEEP OUT OF THE REACH OF CHILDREN.**

**PROTECTIVE CLOTHING:**

Wear adequate protective gear, including gloves and appropriate solvent mask.

**HEALTH & SAFETY:**

Contains petroleum distillates.

**FLAMMABLE:** Keep away from ignition sources (heat, sparks or open flame). Ensure adequate ventilation to prevent build-up of vapours during application and drying.

**NOTICE:** Intentional mis-use by deliberately concentrating and inhaling contents may be harmful. **DO NOT TAKE INTERNALLY.** Avoid contact with eyes, skin and clothing. Can cause irritation.

#### First Aid

**INHALATION:** If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

**INGESTION:** Do not induce vomiting. Get medical attention immediately

**EYE CONTACT:** Flush immediately with water for at least 15 minutes. Get medical attention.

**SKIN CONTACT:** Wash thoroughly with soap and water.



#### Contact Us



**Berger Paints Jamaica Ltd.**  
256 Spanish Town Road,  
P.O. Box 8, Kingston 11, Jamaica  
Tel: +1-876-923-6226  
Fax: +1-876-923-5129  
Email: [bergerja\\_marketing@bergeronline.com](mailto:bergerja_marketing@bergeronline.com)

[www.bergercaribbean.com](http://www.bergercaribbean.com)

 [facebook.com/BergerCaribbean](https://facebook.com/BergerCaribbean)