



### **Product Description**

A fast and easy way to add beautiful colour to unfinished wood. Tintable in hundreds of wood tones and contemporary decorative colours. Fast drying, low odour and easy clean-up with soap and water. For interior and exterior wood. Recommended for floors in combination with a sealer-topcoat such as Polyurethane Varnish.

#### **Surface Preparation**

Surface must be clean and free from dirt, debris, grease, grime and any existing coatings before staining. Sand the wood in the direction of the grain using fine-grade sandpaper until smooth. Do not use steel wool. Remove all sanding dust.

### **Application**

Stir the stain thoroughly before and occasionally during use. No thinning required. Test stain on a small or hidden area of wood to verify desired colour before proceeding to apply the stain. When working with more than one can of the same colour, mix the contents of the cans together to ensure colour consistency. Apply stain with a synthetic bristle brush, foam brush, staining pad or rag. Allow stain to penetrate no longer than 3 minutes. Remove stain that has not penetrated the wood with a clean cloth. Wiping in the direction of the grain using light to medium pressure to achieve even stain colour.

**Note:** For best results, do not allow cloth to become saturated with stain. Replace with clean cloth as necessary. **DO NOT ALLOW STAIN THAT HAS NOT PENETRATED THE WOOD TO DRY ON THE WOOD SURFACE.** Note: Any uneven colour penetration can be blended. Re-wet the surface with more stain and lightly rub the stain into the surface, blending light and dark areas. A second coat my be applied after 1 hour to achieve a darker coat. Light sanding may be required between coats to remove any raised wood grains. For additional protection against dirt, apply a clear protective finish such as **Polyurethane Varnish** (oil-based).

## **Drying Time**

20 minutes. Recoat: 1 hour

Drying times are based on application of thin coats, good ventilation, average temperature of 77°F and 50% relative humidity. Lower average temperature, higher humidity, lack of air movement or excessive application will extend dry time.

# Flash Point

None

# Pack Sizes

3.8 litre, 0.95 litre

### **Colour Range**

Clear

## **Pot Life**

Not applicable

# **Application Tools**

Cloth, synthetic bristle brush or sponge. Coverage 100 sq. ft./ quart.



### **Maintenance**

Mild detergent and water may also be used. Do not use abrasive pads.

## Cleanup / Storage

Clean up with soap and water.

### **Health & Safety**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear appropriate respiratory protection or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

## First Aid

In case of eye contact, flush thoroughly with large amounts of water. Seek medical attention if irritation persists.

If swallowed, go to the nearest hospital emergency room, or physician immediately. DO NOT DRINK. KEEP OUT OF THE REACH OF CHILDREN.



# **Contact Us**



Berger Paints Jamaica Ltd. 256 Spanish Town Road, P.O. Box 8, Kingston 11, Jamaica Tel: +1-876-923-6226 Fax: +1-876-923-5129

Email: bergerja\_marketing@bergeronline.com

www.bergercaribbean.com facebook.com/BergerCaribbean

