



**BERGER**

**BERGER**  
**FLEXI TROWEL**  
ELASTOMERIC TEXTURED FINISH

## PRODUCT DESCRIPTION

**BERGER Flexi Trowel** is a premium quality elastomeric trowel finish with superior permanent flexibility, excellent adhesion and long-term durability for interior and exterior surfaces. This one-coat application is available in Ultra Fine, Fine, Coarse and Ultra Coarse in colours from the Colour Library, in addition to Coral Stone. **BERGER Flexi Trowel** is designed to provide good elasticity and to mask uneven rendered surfaces. It can be applied to previously painted surfaces with the appropriate surface preparation.

## AREAS OF USE

Interior/exterior. For use on concrete, wood, plaster and gypsum board. Not all colours are recommended for exterior use. Consult our website or your BERGER representative for more information.

## PRODUCT PREPARATION

Stir thoroughly before use. No thinning is required.

## SURFACE PREPARATION

**CONCRETE AND OTHER BUILDING SUBSTRATES** Should be dry and free from surface contamination e.g. loose sand, efflorescence, peeling paint. Prime new surfaces if required with BERGER Ultra Fine Flexi Trowel before applying Fine, Coarse or Ultra Coarse for the exterior.

**GLOSS AND EGG-SHELL SURFACES** Should be sanded, flattened and free of dust particles and debris.

**CHALKING AND FLAKING SURFACES** Should be wire brushed to a sound surface.

**NEW SMOOTH CONCRETE** Must be etched before application. Contact the nearest BERGER Technical Representative for more information.

## APPLICATION

Tools required: steel float and plastic trowel. The material is floated evenly over the surface of the substrate with the steel float. Allow to set for 3-15 mins. The plastic trowel is used to create a pattern using a circular motion over the surface.

## DRYING TIME

Touch dry 2 hours, fully dry 24 hours.

## SPREADING RATE

14 m<sup>2</sup> per 5 gallon container; 2.1kg per m<sup>2</sup>. Actual coverage will vary according to texture, surface type and porosity.

## AFTER PAINTING

Clean tools and equipment immediately with clean water. Seal and store unopened containers in a cool dry place.

## DISPOSAL

Do not pour unused product down the drain or onto the ground. Allow it to dry out then dispose of it in the garbage. We however recommend that you donate remaining paints to community organisations and charities.

## SAFETY INSTRUCTIONS

### READ THE FOLLOWING DIRECTIONS CAREFULLY BEFORE USE

**HEALTH AND SAFETY:** Wear adequate protective gear, gloves, goggles, overalls and appropriate respirator. Ensure adequate ventilation while applying; open all windows and doors to facilitate fresh air-flow.

**NOTICE:** Intentional misuse by deliberately concentrating and inhaling contents may be harmful. Do not ingest. Avoid contact with eyes, skin and clothing as this may cause irritation.

### KEEP OUT OF REACH OF CHILDREN AND PETS

## FIRST AID

**INGESTION:** Do not induce vomiting if ingested. Seek medical attention immediately.  
**INHALATION:** If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty with breathing continues, seek immediate medical attention.  
**EYE CONTACT:** Flush immediately with water for about 15 minutes.  
**SKIN CONTACT:** Wash thoroughly with soap and water.

## CONTENTS

Styrene acrylic latex, titanium dioxide, extenders, specialty additives. Lead-free and mercury-free. Low VOC: This product meets VOC compliant standards for semi-gloss emulsions at <60g/L before tinting.

## STORAGE AND HANDLING

Do not apply if precipitation is forecast within 8 hours of product application. Shelf-life in closed containers is 6–9 months when stored in a cool, covered, dry place. Keep pails away from direct sunlight for any extended periods of time.

## LIMITED WARRANTY

BERGER issues this Limited Warranty only to this product when applied to a residence according to label instructions. This Limited Warranty is made to the original consumer/purchaser and is non-transferable. Should the product peel or blister, BERGER or the authorised agent where product was purchased, will at their option and upon proof of purchase, supply replacement coatings to the purchaser in a quantity that is sufficient to repair the specific area of defect or refund the original purchase price.

This Limited Warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the coating, as described in the directions on the label.

BERGER's entire liability shall be limited exclusively to providing replacement coatings for the coating which peels or blisters or the refund of the original purchase price. This Warranty does not include (i) labour and any costs associated with labour for the application and/or removal of any product, and (ii) any indirect, special, incidental or consequential damages.

## CONTACT US



MANUFACTURED BY:  
**BERGER PAINTS BARBADOS LIMITED**

Exmouth Gap, Brandons, St. Michael, Bridgetown, Barbados, W.I. BB12069  
Tel: 246-41-PAINT  
Fax: 246-228-0866  
Email: [info@bergercaribbean.com](mailto:info@bergercaribbean.com)  
Website: [www.bergerpaintscaribbean.com](http://www.bergerpaintscaribbean.com)

