



Product Description

BERGER FLOOR PAINT is a specially formulated 100% acrylic floor coating, specifically designed for use on properly prepared interior and exterior floors, porches, patios, roofs and other wood and cementitious surfaces. Its smooth low sheen finish provides excellent weather resistance, hardness and durability which resists fading, peeling and chipping. It applies easily, is an environmentally friendly, fast-drying coating with excellent coverage. **Berger Water Based Floor Paint** is fungus and mildew resistant, and may be applied to well prepared, previously painted surfaces. It offers excellent product versatility for application and is available in popular standard colours and all Spectra 1800 colours tinted from accent base.

Design Use

Areas of Use: Interior/Exterior
Substrate: Concrete or wooden floors.

Physical Data

Finishes: Glossy
Colour: Tile Red, Delta Green, Ash Grey, Pewter (see the Berger main colour card for colour standards).
Spread Rate: 9 - 10 sq. metre per litre, 350 - 400 sq. ft. per gallon depending on texture and porosity of the surface.
Drying Time: Touch dry in 15 minutes
Recoat time 1 hour
Gloss Levels: Glossy

Application Data

By brush, Roller or Spray.
Coverage: 9 - 10 M2/litre 350 - 400 sq. ft./U.S. gallon.
Drying Time: Touch dry - 1 1/2 - 2hours.
Overcoat - 8 hours
Hard dry - 12 - 16 hours

Additional Information

Thinner: Water. No more than one pint of water to one gallon of floor paint.
Storage Instruction: Store in a cool, shaded dry area.
Flash Point: Not applicable
Shelf Life: Not applicable.
Pack Size: 3.8 litre, 950 ml

Surface Preparation

CONCRETE: Should be swept clean of dirt and loose particles. Grease should be removed by washing with a diluted soap solution, then wash the surface off thoroughly with clean water. Smooth concrete should be treated with Berger Concrete Etching Solution then wash off with clean water before the application of Berger Floor Paint.
Note: Garage floors and carports - Berger Acrylic Floor Paint may be used on garage floors. However, because of hot tyres, the Floor Paint may peel after a period of time at the point of contact. To prevent this, simply place mats where tyres track and rest.

WOODEN FLOOR: Should be cleaned of any dirty or loose particles. flaking paint, was or old polish should be thoroughly scraped off. Floor boards should then be primed with Berger Wood Primer. Knots and pockets of resin should be treated with Knotting Varnish.

Health and Safety

READ INSTRUCTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation.

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced use respiratory protection or leave area for fresh air.

Avoid contact with skin and eyes.

HEALTH & SAFETY: Water based.

First Aid

Ingestion: Do not induce vomiting. Get medical attention immediately.

Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

Eye Contact: Flush immediately with water for at least 15 minutes.

Skin Contact: Wash thoroughly with soap and water.

Recommended Paint Solutions Step 1



Apply 1 or 2 coats **BERGER Floor Paint** to properly prepared surface.

Step 2



After 8 hours drying time, apply another coat of **BERGER Floor Paint**.

Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

www.bergercaribbean.com

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

