



Product Description

Berger 404 Gloss Oil Paint is a premium quality, hard wearing, algae and mildew resistant finish, with excellent stain removal and penetration properties. Specially formulated for exterior and interior surfaces in a tropical environment, Berger 404 Gloss Oil Paint provides good dirt resistance, dries to a smooth, glossy finish and is self-priming on new wood.

Design Use

Areas of use: Interior and Exterior
Substrate: Wood and metal

Physical Data

Finish: Gloss
Colour: 24 Standard (Colour Chart); Colour World Tint System.
Spread Rate: Up to 11sq m/l
Drying Time: Touch, 4 – 6 hours; Hard dry overnight & Recoat, 24 hrs).
Gloss Level: Min 80 gloss units @ 60°. High Gloss

Application Data

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Use up to 250 ml Berger #2 Reducer for ease of application, if required.

Brush or Roller: Apply an even coat taking care to avoid runs and sags.
Spray: Thin 10% with Berger No.2 Reducer. Use conventional spray equipment.

Additional Information

Thinner/clean-up: Berger No.2 Reducer
Storage: Store in a cool, shaded, dry area.
Hazard Rating: Lead-free & non-toxic; Flammable; Flash Point - 37°C (98°F)
Shelf Life: 2 years
Pack Size: Quarts, 1 gallon and 5 gallon cans

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

Wood, Fibreboard, Plyboard

New surfaces

The wood should be low in moisture content (below 15%). Sand all surfaces to a smooth finish. Prime lightly coloured wood with Berger Wood Primer, or Berger Grip & Seal and dark, oily or hard wood with Berger Alkali Sealer or Berger Luxatex Primer. Allow recommended time for drying.

Previously Painted Surfaces

For previously painted surfaces, ensure that dirt, stains, loose material and contaminants, etc. are removed. If the surface is cracking or peeling, remove the loose material by scraping, sanding; glossy surfaces should be abraded. Thoroughly dust down the entire surface.

Treat any fungal growth with Berger Biocidal or Sterilizing Solution. Apply one coat of Berger Wood Primer, Berger Grip & Seal, Berger Alkali Sealer or Berger Luxatex Primer, allowing recommended time for drying.

Gypsum

Sand to a smooth finish and remove all dust. Apply one coat of Berger Alkali Sealer or Berger Luxatex Primer to seal surface, allowing recommended time for drying.

Metal Surfaces

IRON AND STEEL – should be thoroughly cleaned to remove all oil, grease, rust, scale, moisture.

- For conditions of severe marine exposure, Commercial sandblasting to SSPC-6. For conditions of normal exposure - hand or power tool cleaning.
 - For marine and severe exposure, Berger Universal Metal Primer, Berger Navy Protective and Berger Catho Zinc Primer are recommended. For less severe exposures, Berger Red Oxide Primer can be used.
- ALUMINIUM & ZINC – Remove all dirt and grease with an industrial detergent; etch new surfaces with Berger Self Etch Primer; rub down previously painted surfaces with fine grade sandpaper.



BERGER 404 Gloss Oil Paint

Priming

Iron & Steel - Berger Metal Primer, Zinc Chromate (Yellow)
Aluminium & Zinc - Berger Metal Primer Zinc Chromate (yellow). / Self Etch Wash Primer
Wood - Berger Wood Primer Undercoat
 NB: Berger 404 Gloss Oil Paint has self-priming properties, on new wood only.
 When thinned 10% with Berger No.2 Reducer, can be used as self-primer for new wood.
 Contact Berger Technical Service Department for other specific recommendations.

Application

Apply two coats of Berger 404 Gloss Oil Paint to properly prepared new or previously painted surfaces.

Health & Safety

READ DIRECTIONS CAREFULLY BEFORE USE
 Do not take internally. Liquid paint and vapours may cause irritation. Use only with adequate ventilation.
 To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

First Aid

Ingestion: Do not induce vomiting. Get medical attention immediately.
 Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
 Eye Contact: Flush immediately with water for at least 15 minutes.
 Skin Contact: Wash thoroughly with soap and water.

Recommended paint solution for painting new wood Step 1

For priming new wood



Apply 1 coat of **Berger Wood Primer.**

For priming wall close to or by the sea



Apply 1 coat of **BERGER LUXATEX Salt Inhibitive Primer**

Recommended paint solution for painting Metal Step 1

For priming metal



Apply 1 coat of **Berger RustPro Metal Primer**
 On properly prepared Metal.
 Contact Berger Technical for more details

Step 2



Apply 2 coats of **Berger Gloss Oil Paint.**
 Available in thousands of colours through Berger Colour World Advanced Tinting System.

Contact Us



Berger Paints Barbados Ltd.
 Exmouth Gap, Brandons, St. Michael,
 Bridgetown, Barbados, W.I. BB12069
 Tel: +1-246-425-9073
 Fax: +1-246-228-0866
 Email: info@bergeronline.com

www.bergercaribbean.com

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

