



BERGER
A.L.D. Concrete Primer

Product Description

BERGER A.L.D. Concrete Primer is an excellent latex based emulsion primer suitable for new interior/ exterior concrete walls. It has proven economical due to its high solid content which gives it good hiding power and excellent spreading rate.

Design Use

AREAS OF USE: Interior / Exterior
SUBSTRATE: As a primer on new interior and exterior concrete and cement surfaces. Not recommended on exteriors exposed to direct sea blast.

Physical Data

FINISHES: Not applicable
COLOUR: White
SPREAD RATE: Dependent on the temperature and porosity of the surface
DRYING TIME: Touch: 15 Minutes; Recoat: 1 Hour
GLOSS LEVEL: Not applicable

Application Data

By Brush, Roller or Spray. Only use clean tools and equipment.

DRYING TIME: Approximately 15 minutes
MIXING RATIO: 1 litre water per 4 litre A.L.D. Concrete Primer

Additional Information

THINNER: Water
STORAGE: Store in a cool, shaded, dry area
FLASH POINT: Not applicable
SHELF LIFE: Not applicable
PACK SIZE: 20 litres / 4 litres

Surface Preparation

CONCRETE & CEMENT SURFACES - Should be clean and free from dust, damp, grease, wax, loose particles and efflorescence.



Health and Safety

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation.

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

First Aid

INGESTION:

Do not induce vomiting. Get medical attention immediately.

INHALATION:

If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

EYE CONTACT:

Flush immediately with water for at least 15 minutes

SKIN CONTACT:

Wash thoroughly with soap and water

STEP 1



Apply any of the below products for Wall and Concrete

STEP 2



Berger A.L.D. Concrete Primer is also a great primer under Berger 303, Berger Everglow and Berger Magicote Flat Emulsion

Contact Us



Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

