



**BERGER**  
**A.L.D. Concrete Primer**

### Product Description

**BERGER A.L.D. Concrete Primer** is an excellent latex based emulsion primer suitable for new interior/ exterior concrete walls. It has proven economical due to its high solid content which gives it good hiding power and excellent spreading rate.

### Design Use

**AREAS OF USE:** Interior / Exterior  
**SUBSTRATE:** As a primer on new interior and exterior concrete and cement surfaces. Not recommended on exteriors exposed to direct sea blast.

### Physical Data

**FINISHES:** Not applicable  
**COLOUR:** White  
**SPREAD RATE:** Dependent on the temperature and porosity of the surface  
**DRYING TIME:** Touch: 15 Minutes; Recoat: 1 Hour  
**GLOSS LEVEL:** Not applicable

### Application Data

By Brush, Roller or Spray. Only use clean tools and equipment.

**DRYING TIME:** Approximately 15 minutes  
**MIXING RATIO:** 1 litre water per 4 litre A.L.D. Concrete Primer

### Additional Information

**THINNER:** Water  
**STORAGE:** Store in a cool, shaded, dry area  
**FLASH POINT:** Not applicable  
**SHELF LIFE:** Not applicable  
**PACK SIZE:** 20 litres / 4 litres

### Surface Preparation

**CONCRETE & CEMENT SURFACES** - Should be clean and free from dust, damp, grease, wax, loose particles and efflorescence.



**Health and Safety**

**READ DIRECTIONS CAREFULLY BEFORE USE**

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation.

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

**First Aid**

**INGESTION:**

Do not induce vomiting. Get medical attention immediately.

**INHALATION:**

If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

**EYE CONTACT:**

Flush immediately with water for at least 15 minutes

**SKIN CONTACT:**

Wash thoroughly with soap and water

**STEP 1**



**Apply any of the below products for Wall and Concrete**

**STEP 2**



**Berger A.L.D. Concrete Primer is also a great primer under Berger 303, Berger Everglow and Berger Magicote Flat Emulsion**

**Contact Us**



**Berger Paints Barbados Ltd.**  
Exmouth Gap, Brandons, St. Michael,  
Bridgetown, Barbados, W.I. BB12069  
Tel: +1-246-425-9073  
Fax: +1-246-228-0866  
Email: info@bergeronline.com

**Berger Paints Trinidad Ltd.**  
P.O. Box 546, 11 Concessions Road,  
Sea Lots, Port Of Spain, Trinidad  
Tel: +1-868-623-2231  
Fax: +1-868-623-1682

[www.bergercaribbean.com](http://www.bergercaribbean.com) | [facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

