



Product Description

A 100% pure acrylic, water-based, primer, specially formulated with the latest high performance resins for application to a variety of surfaces including concrete, wood, drywall, masonry, aluminium and galvanized metal surfaces. Its superior stain-blocking, sealing qualities, good flash-rust resistance and excellent adhesion make **Berger Grip&Seal Multi-Surface Stain-Blocking Sealer-Primer** an outstanding base coat for the application of topcoats to new and previously painted wall, wood and metal. This versatile primer is fast-drying and can be tinted.

Design Use

AREAS OF USE: Interior / Exterior
SUBSTRATE: Concrete, gypsum, masonry, wood, aluminium and galvanized metal

Physical Data

FINISH: Smooth
COLOUR: White
SPREAD RATE: Wood: 8.5 - 9.0 m²/L
Concrete: 9.0 - 10 m²/L
Metal: 18 - 20 m²/L
DRYING TIME: Touch: 15 Minutes; Recoat: 1 Hour
GLOSS LEVEL: 14 Gloss Units at 60° / Eggshell

Application Data

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Use 250 mls of clean water to 3.8 L for ease of application if necessary.

BRUSH OR ROLLER: Apply an even coat, taking care to avoid runs and sags
SPRAY: Use conventional spray equipment

Additional Information

THINNER: Clean water (if necessary)
STORAGE: Store in a cool, shaded, dry area
FLASH POINT: Not applicable
SHELF LIFE: 1 Year
PACK SIZE: 3.8 L

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation. Ensure that the surfaces to be primed are clean and free from grime, dust and grease. Clean areas severely affected by algae and fungus, thoroughly before applying paint. Clean / treat surfaces which have growth of fungus or algae, with **Berger Biocidal Solution**. Do not apply in wet weather. Not recommended for glazed tiles.

NEW SURFACES

Concrete / Plaster / Mortar Surfaces - Allow surfaces to cure for at least and 7 days for before application. Smooth new surfaces removing all dried and loose particles manually mechanically. Remove dust before application.

Drywall / Gypsum Board - Remove all dust before priming.

Galvanized Metal and Aluminium / Tin - Clean surface with detergent or thinner before application.

Wooden Surfaces - Sand new surfaces to a smooth finish. Counter sink nails in exterior wood work and fill with a water based caulking compound.

PREVIOUSLY PAINTED SURFACES

Remove all cracking, peeling, chalky and flaking paint, by manual or mechanical methods, before application. Treat areas where the surface is bare, as required for new surfaces.



Application

Thin **Grip&Seal** 30% (add 300ml to 1000 ml) before application on metal on hard glossy surfaces. No thinning is required on wood except for ease of application. (250 ml to 3.8 L). In cases of severe staining on wooded surfaces apply an additional coat of primer. Allow one hour of drying before applying the selected topcoat on metal and concrete. Allow two hours of drying before applying the topcoat on wood.

Safety Precautions

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation.

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

First Aid

INGESTION:

Do not induce vomiting. Get medical attention immediately.

INHALATION:

If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

EYE CONTACT:

Flush immediately with water for at least 15 minutes

SKIN CONTACT:

Wash thoroughly with soap and water

STEP 1



Apply any of the below products for Wall, Wood and Metal

STEP 2



Berger Grip&Seal is also a great primer under Berger 303, Berger Everglow and Berger Magicote Flat Emulsion

Contact Us



Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.



REF: G&S-01/2016

BERGER
grip&seal Multi-Surface Stain-Blocking Sealer & Primer