



BERGER Luxatex Salt Inhibitive Sealer Primer

Product Description

Berger Salt Inhibitive Primer is a professional quality, salt-blocking, solvent based, primer and sealer specially formulated to provide long-term resistance and an effective seal to prevent the reaction of alkali salts with topcoats. For use on interior and exterior wall, timber and concrete surfaces, in general maintenance. Luxatex is also ideal for priming and sealing uncured or "green" concrete. Luxatex is easy to apply, provides excellent coverage, spreads evenly, resists sagging, and has excellent levelling and anti-carbonation properties and dries quickly to a smooth finish. In addition, Luxatex penetrates into surface pores to provide excellent adhesion for topcoats. As a versatile primer, Luxatex can be over-coated with oil or water based paints.

Design Use

AREAS OF USE: Interior / Exterior
SUBSTRATE: Concrete, plaster, masonry, brickwork, blockwork, may also be used on Timber and metal surfaces.

Technical Data

FINISH: Smooth
COLOUR: White
VOLUME SOLIDS: 42%
THINNER/CLEANER: Solvalux 7-25 or Berger Reducer #4
COVERAGE: 5 m² - 6 m² per litre depending on porosity of surface.
SPREAD RATE: While estimating the practical spread rates, due allowance should be made for surface profile, uneven application, overspray, losses in containers and equipment.
DRYING TIME: Touch dry: 1/2 Hour; Recoat: 12 Hours
HEAT RESISTANCE: Withstands dry heat up to 80° C
BS 6150 REFERENCE: Meets performance of 3/1

Application Method

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply coating when surface temperature is 3°C or more above dew point. Use 5% to 10% thinner for ease of application depending on the method of application. Wash equipment with Berger Reducer #4.

AIRLESS SPRAY: Tip Size: 0.22 – 0.30 mm (0.008 – 0.012 in)
Tip pressure: 100 – 140 kg/cm² (1300 – 2000 psi)
CONVENTIONAL SPRAY: Use normal spray equipment suitable for low viscosity paint at an atomizing pressure of 2.8 – 3.0 kg/cm² (40-45 psi).
BRUSH OR ROLLER: Apply an even coat, taking care to avoid runs and sags

Storage and Handling

STORAGE: Store in a cool, shaded, dry area
DISPOSAL: Dispose as normal paint e.g., by controlled landfill. In case of doubt consult local authority. Do not empty into drains, sewer or other water courses.
FLASH POINT: 37°C, 98°F
SPECIFIC GRAVITY: 1.32 ± 0.02
SHELF LIFE: Up to 12 Months
PACK SIZE: 3.8 L

Surface Preparation

Ensure surface is thoroughly clean and dry before painting. Concrete and cement surface should be clean and free from dust, damp, grease loose particulars and efflorescence.

Very strong alkaline surfaces may require two (2) coats.

Can be top coated with any Berger topcoat such as Royale, Weatherproof, 303 Flat, Everglow Low Sheen, 404 Gloss, Flat, Semi-Gloss, High Gloss Enamel, Industrial Enamel, Marine, etc.



BERGER Luxatex Salt Inhibitive Sealer Primer

Safety Precautions

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation.

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

First Aid

INGESTION:

Do not induce vomiting. Get medical attention immediately.

INHALATION:

If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

EYE CONTACT:

Flush immediately with water for at least 15 minutes

SKIN CONTACT:

Wash thoroughly with soap and water

STEP 1



Apply 1 or 2 even coats of **Berger Luxatex Salt Inhibitive Sealer Primer** to properly prepared surface.

STEP 2



BERGER Luxatex Salt Inhibitive Sealer Primer can also be applied under **Berger Magicote Gloss Paint, Berger Marine Enamel** and **Berger 303 Flat Emulsion**.

Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com | [facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

