



BERGER
Magicote Flat Emulsion

Product Description

BERGER MAGICOTE FLAT EMULSION is an easy to use flat emulsion paint. This product has been specifically formulated to withstand the harsh tropical weather, and is ideal for inside and outside use.

Design Use

AREAS OF USE: Interior / Exterior
SUBSTRATE: New plaster, brickwork, cement rendering, concrete, Asbestos sheets, plaster board and primed metal surfaces.

Physical Data

FINISH: Flat
COLOUR: Supplied in 13 standard colours, inclusive of white
SPREAD RATE: 4.2 sq. metres / 3.8 litres; 11 sq. metres per litre
N.B. Will vary according to the texture of the surface to which it is applied.
DRYING TIME: Touch: 15 Minutes; Recoat: 1 Hour
GLOSS LEVEL: Not applicable

Application Data

By brush, Roller or Spray. For spray application, thin as necessary with water. First coat on unpainted surface may be thinned with up to 1/2 pint of clean water to the gallon

DRYING TIME: Approximately 15 minutes

Should not be used over limeash, oil, bound distemper or efflorescing surfaces, unless these are specially treated.

Additional Information

THINNER: Water. Use no more than 250ml of clean water to the 3.8 litre container. Clean equipment immediately with water.
STORAGE: Store in a cool, shaded, dry area
FLASH POINT: Not applicable
SHELF LIFE: Not applicable
PACK SIZE: 1 U.S. gallon, 3.8 litres

Surface Preparation

CONCRETE & CEMENT SURFACES Should be clean and free from dust, damp, grease wax, loose particles and efflorescence.
IRON AND STEEL Should be thoroughly cleaned to remove all oil, grease, rust, scale and moisture.
ALUMINIUM & ZINC WOOD Should be degreased and treated with Berger Self Etch Primer. Should be rubbed down with sandpaper and all knots and resin pockets treated with two (2) thin coats of Berger Knotting Varnish. Should be free from loose sand, mortar splashes, efflorescence.
CONCRETE & CEMENT PREVIOUSLY OIL-PAINTED AREAS Clean thoroughly to remove all dirt, grease, etc. Remove all loose and flaking material rub down with fine grade sandpaper and touch up with the appropriate Berger Primer.
PREVIOUSLY LIME-WASHED OR DISTEMPERED SURFACE Clean, scrape and wire brush thoroughly, then apply one coat of Berger Penetrating Liquid, or Berger Alkali Sealer.
PRIMING: IRON & STEEL Berger Red Oxide Metal Primer recommended.
ALUMINIUM & ZINC WOOD Berger Zinc Chromate Metal Prime
Berger White Wood Primer Undercoat
CONCRETE, CEMENT, ETC. No priming required. However, the use of 1 coat of Berger Alkali Sealer on new concrete surface, especially on the exterior will prevent efflorescence.



Health and Safety

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation.

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air.

Avoid contact with skin or eyes.

First Aid

INGESTION:

Do not induce vomiting. Get medical attention immediately.

INHALATION:

If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

EYE CONTACT:

Flush immediately with water for at least 15 minutes

SKIN CONTACT:

Wash thoroughly with soap and water

STEP 1

PRIMER For new Wood



Apply 1 coat
of BERGER Grip&Seal
Multi-Surface Sealer & Primer

PRIMER For new Wall



Apply 1 coat
of BERGER Concrete Primer

STEP 2



Apply 1 or 2 coats of BERGER Magicote
Flat Emulsion to
properly prepared surface.

Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com | facebook.com/BergerCaribbean

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

