



### Product Description

**BERGER MAGICOTE FLAT EMULSION** is an easy to use flat emulsion paint. This product has been specifically formulated to withstand the harsh tropical weather, and is ideal for inside and outside use.

### Design Use

**AREAS OF USE:** Interior / Exterior  
**SUBSTRATE:** New plaster, brickwork, cement rendering, concrete, Asbestos sheets, plaster board and primed metal surfaces.

### Physical Data

**FINISH:** Flat  
**COLOUR:** Supplied in 13 standard colours, inclusive of white  
**SPREAD RATE:** 4.2 sq. metres / 3.8 litres; 11 sq. metres per litre  
N.B. Will vary according to the texture of the surface to which it is applied.  
**DRYING TIME:** Touch: 15 Minutes; Recoat: 1 Hour  
**GLOSS LEVEL:** Not applicable

### Application Data

By brush, Roller or Spray. For spray application, thin as necessary with water. First coat on unpainted surface may be thinned with up to 1/2 pint of clean water to the gallon

**DRYING TIME:** Approximately 15 minutes

Should not be used over limeash, oil, bound distemper or efflorescing surfaces, unless these are specially treated.

### Additional Information

**THINNER:** Water. Use no more than 250ml of clean water to the 3.8 litre container. Clean equipment immediately with water.  
**STORAGE:** Store in a cool, shaded, dry area  
**FLASH POINT:** Not applicable  
**SHELF LIFE:** Not applicable  
**PACK SIZE:** 1 U.S. gallon, 3.8 litres

### Surface Preparation

<b>CONCRETE &amp; CEMENT SURFACES</b>	Should be clean and free from dust, damp, grease wax, loose particles and efflorescence.
<b>IRON AND STEEL</b>	Should be thoroughly cleaned to remove all oil, grease, rust, scale and moisture.
<b>ALUMINIUM &amp; ZINC WOOD</b>	Should be degreased and treated with Berger Self Etch Primer. Should be rubbed down with sandpaper and all knots and resin pockets treated with two (2) thin coats of Berger Knotting Varnish
<b>CONCRETE &amp; CEMENT PREVIOUSLY OIL-PAINTED AREAS</b>	Should be free from loose sand, mortar splashes, efflorescence. Clean thoroughly to remove all dirt, grease, etc. Remove all loose and flaking material rub down with fine grade sandpaper and touch up with the appropriate Berger Primer.
<b>PREVIOUSLY LIME-WASHED OR DISTEMPERED SURFACE PRIMING: IRON &amp; STEEL</b>	Clean, scrape and wire brush thoroughly, then apply one coat of Berger Penetrating Liquid, or Berger Alkali Sealer. Berger Red Oxide Metal Primer recommended.
<b>ALUMINIUM &amp; ZINC WOOD</b>	Berger Zinc Chromate Metal Prime Berger White Wood Primer Undercoat
<b>CONCRETE, CEMENT, ETC.</b>	No priming required. However, the use of 1 coat of Berger Alkali Sealer on new concrete surface, especially on the exterior will prevent efflorescence.

**Health and Safety**

**READ DIRECTIONS CAREFULLY BEFORE USE**

Do not take internally.  
Liquid paint and vapours may cause irritation.  
Use only with adequate ventilation.  
To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air.  
Avoid contact with skin or eyes.

**First Aid**

**INGESTION:** Do not induce vomiting. Get medical attention immediately.  
**INHALATION:** If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.  
**EYE CONTACT:** Flush immediately with water for at least 15 minutes  
**SKIN CONTACT:** Wash thoroughly with soap and water

**STEP 1**

**PRIMER  
For new Wood**



**Apply 1 coat  
of BERGER Wood Primer**

**PRIMER  
For new Wall**



**Apply 1 coat  
of BERGER Concrete Primer**

**STEP 2**



**Apply 1 or 2 coats of BERGER Magicote  
Flat Emulsion to  
properly prepared surface.**

**Contact Us**



**Berger Paints Jamaica Ltd.**  
256 Spanish Town Road,  
P.O. Box 8, Kingston 11, Jamaica  
Tel: +1-876-923-6226  
Fax: +1-876-923-5129  
Email: bergerja\_marketing@bergeronline.com

[www.bergercaribbean.com](http://www.bergercaribbean.com)  
[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

