



### Product Description

**BERGER MAGICOTE GLOSS OIL PAINT** is ideal for interior and exterior uses where a high quality gloss paint with polyurethane, excellent gloss retention and durability is desired.

### Design Use

**AREAS OF USE:** Interior / Exterior  
**SUBSTRATE:** Wood, concrete, primed metal surfaces (iron, steel, aluminium, zinc).

### Physical Data

**FINISH:** Gloss  
**COLOUR:** Supplied in 16 standard colours, inclusive of black and white  
**SPREAD RATE:** 8.0-8.5 sq. metres per litre, 360-390 sq. feet per gallon  
N.B. Will vary according to the texture of the surface to which it is applied.  
**DRYING TIME:** Touch: 4 Hours; Recoat: 18 Hours; Hard Dry: 24 Hours  
**GLOSS LEVEL:** High Gloss

### Application Data

By brush, Roller or Spray. For spray application, thin as necessary with Berger No. 2 Reducer. First coat on unpainted surface may be thinned appropriately with Berger No. 2 Reducer to the gallon.

### Additional Information

**THINNING/CLEAN UP:** Berger Reducer No. 2  
**STORAGE:** Store in a cool, shaded, dry area  
**FLASH POINT:** 36.7° C, 98°F  
**SHELF LIFE:** Not applicable  
**PACK SIZE:** 1 US gallon, Quarts, 4 litres, 1 litre

### Surface Preparation

**CONCRETE & CEMENT SURFACES** Should be clean and free from dust, damp, grease wax, loose particles and efflorescence.

**IRON AND STEEL** Should be thoroughly cleaned to remove all oil, grease, rust, scale and moisture.

**ALUMINIUM & ZINC** Should be degreased and treated with Berger Self Etch Primer.  
**WOOD** Should be rubbed down with sandpaper and all knots and resin pockets treated with two (2) thin coats of Berger Knotting Varnish

**CONCRETE & CEMENT** Should be thoroughly dry and free from loose sand and efflorescence.

**PREVIOUSLY PAINTED SURFACES** Should be thoroughly clean and free from flaking paint.

**PRIMING:**  
**Iron and Steel** - Berger Red Oxide Metal Primer.  
**Wood** - Berger White Wood Primer Undercoat.  
**Concrete** - Berger Alkali Sealer.

**Health and Safety**

**READ DIRECTIONS CAREFULLY BEFORE USE**

Do not take internally.  
Liquid paint and vapours may cause irritation.  
Use only with adequate ventilation.  
To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air.  
Avoid contact with skin or eyes.

**First Aid**

**INGESTION:** Do not induce vomiting. Get medical attention immediately.  
**INHALATION:** If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.  
**EYE CONTACT:** Flush immediately with water for at least 15 minutes  
**SKIN CONTACT:** Wash thoroughly with soap and water

**STEP 1**

**PRIMER**  
For new Wood



Apply 1 coat of  
**BERGER Wood Primer**

**PRIMER**  
For new Wall



Apply 1 coat of  
**BERGER Concrete Primer**

**PRIMER**  
Iron and Steel



Apply 1 coat of  
**BERGER Red Oxide Metal Primer**

**STEP 2**



Apply 1 or 2 coats of **BERGER Magicote Gloss Oil Paint** to properly prepared surface.

**Contact Us**



**Berger Paints Jamaica Ltd.**  
256 Spanish Town Road,  
P.O. Box 8, Kingston 11, Jamaica  
Tel: +1-876-923-6226  
Fax: +1-876-923-5129  
Email: bergerja\_marketing@bergeronline.com

[www.bergercaribbean.com](http://www.bergercaribbean.com)

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

