



Product Description

BERGER MAGICOTE GLOSS OIL PAINT is ideal for interior and exterior uses where a high quality gloss paint with polyurethane, excellent gloss retention and durability is desired.

Design Use

AREAS OF USE: Interior / Exterior
SUBSTRATE: Wood, concrete, primed metal surfaces (iron, steel, aluminium, zinc).

Physical Data

FINISH: Gloss
COLOUR: Supplied in 16 standard colours, inclusive of black and white
SPREAD RATE: 8.0-8.5 sq. metres per litre, 360-390 sq. feet per gallon
N.B. Will vary according to the texture of the surface to which it is applied.
DRYING TIME: Touch: 4 Hours; Recoat: 18 Hours; Hard Dry: 24 Hours
GLOSS LEVEL: High Gloss

Application Data

By brush, Roller or Spray. For spray application, thin as necessary with Berger No. 2 Reducer. First coat on unpainted surface may be thinned appropriately with Berger No. 2 Reducer to the gallon.

Additional Information

THINNING/CLEAN UP: Berger Reducer No. 2
STORAGE: Store in a cool, shaded, dry area
FLASH POINT: 36.7° C, 98°F
SHELF LIFE: Not applicable
PACK SIZE: 1 US gallon, Quarts, 4 litres, 1 litre

Surface Preparation

CONCRETE & CEMENT SURFACES Should be clean and free from dust, damp, grease wax, loose particles and efflorescence.

IRON AND STEEL Should be thoroughly cleaned to remove all oil, grease, rust, scale and moisture.

ALUMINIUM & ZINC Should be degreased and treated with Berger Self Etch Primer.
WOOD Should be rubbed down with sandpaper and all knots and resin pockets treated with two (2) thin coats of Berger Knotting Varnish

CONCRETE & CEMENT Should be thoroughly dry and free from loose sand and efflorescence.

PREVIOUSLY PAINTED SURFACES Should be thoroughly clean and free from flaking paint.

PRIMING:
Iron and Steel - Berger Red Oxide Metal Primer.
Wood - Berger White Wood Primer Undercoat.
Concrete - Berger Alkali Sealer.



Health and Safety

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.
Liquid paint and vapours may cause irritation.
Use only with adequate ventilation.
To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air.
Avoid contact with skin or eyes.

First Aid

INGESTION:	Do not induce vomiting. Get medical attention immediately.
INHALATION:	If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
EYE CONTACT:	Flush immediately with water for at least 15 minutes
SKIN CONTACT:	Wash thoroughly with soap and water

STEP 1

PRIMER For new Wood



Apply 1 coat of
BERGER Grip&Seal
Multi-Surface
Sealer & Primer

PRIMER For new Wall



Apply 1 coat of
BERGER
Concrete Primer

PRIMER Iron and Steel



Apply 1 coat of
BERGER
Red Oxide
Metal Primer

STEP 2



Apply 1 or 2 coats of **BERGER Magicote Gloss Oil Paint** to properly prepared surface.

Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com | facebook.com/BergerCaribbean

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

