



Product Description

BERGER PENETRATING LIQUID is a clear processed oil medium with specially selected solvents to assist penetration.

Design Use

Areas of Use: Interior/Exterior
Substrate: Use to bind loose and powdery materials prior to the application of Emulsion paint on wood and other surfaces which are not Alkaline.

Physical Data

Finishes: Not applicable
Colour: Clear
Spread Rate: 9 - 10 sq. metre per litre, 350 - 400 sq. ft. per gallon depending on texture and porosity of the surface.
Drying Time: To touch in 2 hours
Recoat in 18 hours
Gloss Levels: Not applicable

Application Data

Methods: Brush, Roller or Spray
Coverage: 9 - 10 sq. metre per litre, 350 - 400 sq. ft. per U.S. Gallon
Drying Time: Touch dry - 1 1/2 - 2 hours
Overcoat - 8 hours
Hard dry - 12 - 16 hours

Additional Information

Thinner: Berger No. 2 Reducer
Storage Instructions: Store in a cool, shaded dry area
Flash Point: 37°C (98°F)
Shelf Life: Not applicable
Pack Sizes: 3.8 litre, 950 ml

Surface Preparation

Although **Berger Penetrating Liquid** will penetrate at least 1/8th of an inch into the surface, it is recommended that all old coatings are removed by scraping and wire brushing so that the material will thoroughly bind remaining materials to the basic surface to prevent flaking and peeling.



Health and Safety Instructions

READ INSTRUCTIONS CAREFULLY BEFORE USE.

Do not take internally. Liquid paint and vapours may cause irritation. Use only with adequate ventilation. To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced use respiratory protection or leave area for fresh air. Avoid contact with skin and eyes.

HEALTH & SAFETY: Solvent based.

First Aid

- Ingestion:** Do not induce vomiting. Get medical attention immediately.
- Inhalation:** If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
- Eye Contact:** Flush immediately with water for at least 15 minutes.
- Skin Contact:** Wash thoroughly with soap and water.

**RECOMMENDED PAINT SOLUTIONS
STEP 1**



Apply 1 or 2 coats of **Berger Penetrating Liquid** to properly prepared surface.

STEP 2



Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com | [facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

