



BERGER Roof Compound

Product Description

BERGER ROOF COMPOUND is a highly flexible water-proofing emulsion coating which is ideally suited for preventing and stopping leaks on concrete, aluminium or galvanized zinc roofs and around nail heads. It is totally weatherproof. It stretches and moves with temperature changes, especially over seams. It dries to a flexible, skin-tight seal against weather.

Design Use

Areas of Use: Exterior
Substrate: Concrete, aluminium, or zinc (galvanized iron), nailheads on metal roofs.

Physical Data

Finishes: Not applicable
Colour: Not applicable
Spread Rate: Not applicable
Drying Time: Touch-dry: 3 hours
To recoat: 24 hours
Gloss Levels: Not applicable

Application Data

Use rollers, squeegee, airless-spray or brush.

Coverage: Minimum recommendation: 40 sq. ft. per gallon at film thickness
Wet - 45 mils
Dry - 25 mils
Drying Time: Touch-dry: 3 hours
To recoat: 24 hours

Additional Information

Thinner: Not applicable
Storage Instructions: Store in a cool, shaded dry area
Flash Point: Not applicable
Shelf Life: Not applicable
Pack Size: 3.8 litre

Surface Preparation

Wide cracks should be filled using a mixture containing 1 part Roofing Compound and 2 to 3 parts building sand (150 mesh). The first coat is a roller applied in one direction after diluting 4 parts Roofing Compound with 1 part water to improve penetration and adhesion. Active, shiftinor wide cracks, which have already been filled should be reinforced by laying a polyester gauze (mesh) over the crack, after applying the first coat. The gauge (mesh) is then saturated with about 5% thinned Roofing Compound (1/2 pint water to 1 gallon Roofing Compound) and allowed to dry overnight. The second coat is applied as supplied without thinning after 24 hours drying. The coating is applied in one direction, but at right angle to the direction of the first coat's application.

Health and Safety Instructions

READ INSTRUCTIONS CAREFULLY BEFORE USE.

Do not take internally. Liquid paint and vapours may cause irritation. Use only with adequate ventilation. To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced use respiratory protection or leave area for fresh air. Avoid contact with skin and eyes.

First Aid

Ingestion: Do not induce vomiting. Get medical attention immediately.
Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
Eye Contact: Flush immediately with water for at least 15 minutes.
Skin Contact: Wash thoroughly with soap and water.

RECOMMENDED PAINT SOLUTIONS
STEP 1



Apply a thin coat of **Berger Roof Compound** to properly prepared surface.

STEP 2



After 24 hours drying time, apply a normal coat of **Berger Roof Compound** at right angle to 1st coat.

Contact Us



Berger Paints Barbados Ltd.
 Exmouth Gap, Brandons, St. Michael,
 Bridgetown, Barbados, W.I. BB12069
 Tel: +1-246-425-9073
 Fax: +1-246-228-0866
 Email: info@bergeronline.com

www.bergercaribbean.com

 facebook.com/BergerCaribbean

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

