



Product Description

With its soft touch and smooth sheen **Berger royale** brings walls to life with the elegance and feel of exotic fabrics. Combined with the traditional attributes of a superior paint, virtually odourless and specially formulated with carefully selected raw materials, **Berger royale** incorporates **Dura-Tuf** Technology, making it tough to stain, easy to clean and highly resistant to fungus and algae, whilst maintaining its beauty for 7 years.

Design Use

Areas of use: Interior
Substrate: Concrete, Plaster, Masonry

Physical Data

Finishes: Silk
Colour: White & Colour-World Tint System
Spread Rate: Approximately 42m² per US 1 Gallon (3.8 Litres) container on previously painted surfaces.
Drying Time: Touch - 15 minutes
Recoat - 1 hour
Gloss levels: Silk

Application Data

By brush, roller or spray. Only use clean tools and equipment. When applying by brush and roller apply an even coat to avoid runs and sags. Apply two coats. Remove any paint drops immediately with clean water.

Drying Time: Approximately 15 minutes. Recoat after 1 hour.

Additional Information

Thinner: Clean water
Storage Instruction: Store in a cool, shaded, dry area.
Flash point: Not Applicable
Shelf Life: 2 years
Pack Size: US 1 Gallon (New) 3.8 Litres

Surface Preparation

Ensure surface is clean, dry and free from fungus, dirt, grease, efflorescence and all other contaminants. Peeling paint and chalk must be removed. Remove efflorescence, fungus, chalk and peeling paint by wire brush or sweep blast. Smooth new surfaces with sand paper, and dust down to remove all loose particles. Seal with Alkali Sealer.

Allow at least 1 hour drying for Berger Grip & Seal Multisurface Primer Sealer before applying royale. Allow overnight drying when using Alkali Sealer. If the surface is previously painted ensure that dirt, stain, etc. and other loose material and contaminants are removed.

Treat fungal growth if any with Berger Sterilizing Solution. To achieve a very smooth surface, apply one or two coats of Berger Uno-Shield to fill holes, cracks and imperfections. Smooth surface by sanding. Seal with Berger Alkali Sealer. Apply 1 to 2 coats of Berger royale silk. Some colours will require a suitably tinted primer for best results.

Health & Safety

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use with adequate ventilation

To ensure the entry of fresh air, open all windows and doors if headache or dizziness is experienced.

Leave area for fresh air.

Avoid contact with skin or eyes.

First Aid

Ingestion: Do not induce vomiting. Get medical attention immediately

Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air.

If difficulty continues, seek immediate medical attention.

Eye Contact: Flush immediately with water for at least 15 minutes.

Skin Contact: Wash thoroughly with soap and water.

Recommended paint solutions

Step 1

PRIMER
For New Wall & Wood



Apply 1 Coat

TINT US 1 GALLON (New)
(3.8 Litres) CAN SIZE

Step 2



Apply 2 coats of Berger Royale Silk

Contact Us



Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.