



BERGER TROWEL-ON Textured Finishes

Product Description

Trowel-On is a heavy-bodied, textured finish available in four textures, for exterior and interior use. **Berger Trowel-On** is one-coat application gives an attractive textured surface which protects and obliterates concrete and rendered walls. It is ideally suited to mask uneven rendered surfaces and will cover imperfections and hide irregularities of the substrates. It is used as a one coat finish on new work, previously coated surfaces and flush pointed block work.

Design Use

AREAS OF USE: Interior / Exterior
SUBSTRATE: Concrete, rendered surfaces, plywood, wood and wall paper and plaster boards.

Grades Available

FINISH: Ultra Fine, Fine, Coarse, Ultra Coarse

Product Characteristics

1. Excellent resistance to algae and mildew.
2. Touch dry in 15 - 30 minutes. Hard dry in 24 hours.
3. One coat application.
4. Excellent opacity.
5. Fills surface imperfections and covers cracks, etc.
6. Hard, tough, abrasive resistance, long life, decorative appeal and all round adaptability.
7. Available in hundreds of colours in the Spectra 1800 fandeck.

Surface Preparation

RENDERING, CONCRETE AND OTHER BUILDING SUBSTRATES: Should be dry and free from surface contamination e.g. loose and efflorescence, peeling paint.

PREVIOUSLY PAINTED SURFACES - Should be clean.

GLOSS & EGG SHELL SURFACES - Should be abraded.

FRIABLE AND FLAKING SURFACES - Should be wire-brushed to sound surfaces.

NEW SMOOTH CONCRETE - Must be etched, using Berger Concrete Etching Solution. Rinse surface after 30 minutes and allow to dry before applying Berger Trowel-On.

Application

Applied by a trained professional, by plastering technique in two steps: (1) with stainless steel trowel, allowed to set for 10 minutes. The setting time is dependent on air temperature and humidity. Step (2) a plastic float is used to deliver a decorative scratch finish texture for interior and exterior application on Commercial and Residential properties. Different patterns are achieved with different techniques.

Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com | [facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.



REF: TRO-11/2015