



Product Description

Berger Wood Primer is a versatile, white primer, made especially for exterior and interior application to resinous and oily woods, plywood and hardboard surfaces. Its penetrating and sealing properties make it a great primer for bare wood and providing great adhesion to topcoats. In addition Berger Wood Primer White inhibits the growth of fungus and mildew on the surface.

Design Use

AREAS OF USE: Interior /Exterior. Specially formulated for resinous and oily woods. It is also recommended for use on plywood and chipboard.

Technical Data

FINISH: Semi Gloss
COLOUR RANGE: White
THINNER/CLEANER: Berger Reducer No. 2.
SPREADING RATE: 7-9 sq. metres per litre, 300-350 sq. feet per gallon.
DRYING TIME: Touch Dry - 4 hours. Recoat - 24 hours.
FLASH POINT: 36.7°C, 98°F
POT LIFE: Not applicable
PACK SIZES: 3.8 litre, 0.95 litre

Application Method

Brush

Surface Preparation

The wood should be thoroughly dry and clean and rubbed down to a smooth surface with a fine sandpaper, all dust and debris should then be removed. Knots and resin pockets should be treated with one or preferably two thin coats of Berger Knotting Varnish.

Safety Precautions

READ DIRECTIONS CAREFULLY BEFORE USE

Do not take internally.

Liquid paint and vapours may cause irritation.

Use only with adequate ventilation.

To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

First Aid

INGESTION: Do not induce vomiting. Get medical attention immediately.

INHALATION: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

EYE CONTACT: Flush immediately with water for at least 15 minutes

SKIN CONTACT: Wash thoroughly with soap and water

Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

www.bergercaribbean.com

[facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



REF:WOOD-PRIME-11/2015

BERGER
White Wood Primer / Undercoat