



Product Description

For centuries, oil-based enamel has been the professional painters' only choice for painting and trimming wood and metal. Technologically advanced Berger royale Water-Based Luxury Gloss Enamel, has now changed the oil paint landscape forever, with comparable performance in flow, levelling, adhesion, print, block and abrasion resistance. As a water-borne formulation, Berger royale Gloss Enamel is non-yellowing, low-odour, recoats in 1 hour, and is lead and mercury-free. These unique properties make Berger royale Luxury Gloss Enamel, the ideal environmentally-friendly alternative to oil-paint on wood, with a durability designed to wow even die-hard oil-paint fans. Used in conjunction with Berger grip&seal Multi Surface Primer Sealer, Berger royale Water-Based Luxury Gloss Enamel is also a great solution for interior metal, providing excellent protection against wear and rust and is tintable in all of the Pastel, Deep and Accent Base colours in the Berger Spectra 1800 fandeck.

Physical Data

- Excellent durability
- For wood and concrete
- Abrasion resistant
- Superior fungus resistance
- Block resistant
- Water resistant
- Excellent flow and leveling properties
- Non-yellowing
- Easy cleanup with water

Additional Information

| | |
|--------------------------------|--|
| Colors Available: | White & colours in the BERGER Colour World Tinting System |
| Gloss: | Gloss |
| Thinning/Clean up: | Water |
| Recommended Use: | Interior |
| Recommended for use on: | Doors, trim, cabinets, walls, cupboards and ceilings. For primed or previously painted wallboard, plaster, masonry, wood and metal. |

Surface Preparation

Surface to be painted must be clean and free from all dust, dirt, grease, and any contamination. Scrape and sand loose and flaking paint and feather edges to a uniform profile. New concrete must be allowed to cure for at least 30 days before priming. If painting uncured concrete, use Berger Luxatex Primer one week after plastering. Clean the surface to remove mould or fungus and treat with Berger Sterilizing Solution. Do not remove on concrete. Remove after one hour on wood. Treat chalky surfaces with Berger Alkali Sealer or Berger Penetrating Liquid. Allow the surface to dry before applying Berger grip & seal Multi-Surface Primer Sealer. Allow to dry before the application of topcoat. Metal: Remove all rust and treat metal surfaces properly, then apply Berger grip & seal Multi-Surface Primer Sealer and allow to dry two hours before application of Berger royale Water-Based Luxury Gloss Enamel.

Application

Brush, roller or spray. If required, thin with no more than 200ml/3.8L. When applying by brush, (1) Ensure that the brush is fairly loaded with paint. (2) Use the minimum brush strokes and feather lightly. Avoid excessive brushing as this will leave brush marks.

| | |
|---------------------------|---|
| Spreading Rate: | 37- 42 sq metres per 3.8 litres. |
| Drying: | Touch: 20 minutes. Hard: 2 hours. Recoat: 2 hours |
| Thinning/Clean up: | Water |
| Pack Sizes: | 1 Litre, 4 Litre, 19 Litre |
| Colour Range: | White and hundreds of colours through the Berger Colour World Advanced Tinting System |



Health & Safety

Keep out of the reach of children. Wear adequate protective gear, gloves, goggles, overalls and the appropriate respirator. Use only with adequate ventilation. To ensure fresh air entry, open all windows and doors.

Notice: Intentional misuse by deliberately concentrating and inhaling contents may be harmful. Do not take internally. Avoid contact with eyes, skin and clothing. Can cause irritation.

First Aid

- Ingestion:** DO NOT INDUCE VOMITING. Seek medical attention immediately.
- Inhalation:** If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
- Eye Contact:** Flush immediately with water for at least 15 minutes.
- Skin Contact:** Wash thoroughly with soap and water.

Step 1



Recommended paint solution for painting new wood, wall or metal surface:

Apply 1 coat of **Berger grip&seal Multi-Surface Primer Sealer**. A quick drying, water-based primer for many surfaces.

Step 2



Apply 2 coats of **Berger royale Water-Based Luxury Gloss Enamel**.

Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com |  facebook.com/BergerCaribbean

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

