



Product Description

Berger Woodtech Marine Spar Varnish is an alkyd modified, chlorinated rubber-based varnish, specially formulated to give a warm, amber tone and bring out the natural beauty of wooden surfaces, with a finish that performs even in the harshest conditions.

Berger Woodtech Marine Spar Varnish is a tough, flexible, long lasting coating made to provide protection against sun, weather, sea spray and mildew. **Berger Woodtech Marine Spar Varnish** is easy to apply and re-apply over old varnish in reasonably good condition.

Areas of Use

Berger Woodtech Marine Spar Varnish gives a traditional high gloss finish to marine vessels. It is also suited for the exterior of Windows, Doors and Frames and Wooden Garden Furniture that face the onslaught of sun and rain 24 hours a day.

Surface Preparation

Surface must be clean, dry, smooth and free from dirt, grease wax and old paint. New wood should be thoroughly dry. Previously varnished surfaces in poor condition should be thoroughly stripped Rub down to a smooth surface with fine sandpaper.

Before Use

Always stir **Berger Woodtech Marine Spar Varnish** thoroughly.

Application

Apply liberally with a clean brush or spray. 2 coats should be applied on varnished wood if surface is sound or 3 to 4 coats on new wood. After application, **Berger Woodtech Marine Spar Varnish** will be 'touch dry' in 4 hours. Additional coats should only be applied after a drying time of 12 hours.

Thinning / Clean up

Clean equipment immediately with **Berger No. 3 Reducer**. Store in a cool place. Keep away from children.

Spreading Rate

9.0-9.5 sq. metres per litre, 375-400 sq. ft / Gallon, depending on the porosity and texture of the surface.

Drying Time

Touch Dry: 2 Hours.

Recoat: 12 Hours.

Hard Dry: 24 Hours.

Pack Sizes

4 litre, 1 litre | U.S. Gallon, 1 Quart.

Colour Range

Clear

Packaging

4 Litre



Flash Point

37°C (98°F)

Pot Life

Not applicable

Health & Safety

KEEP OUT OF THE REACH OF CHILDREN.

PROTECTIVE CLOTHING:

Wear adequate protective gear, including gloves and appropriate solvent mask.

HEALTH & SAFETY:

Contains petroleum distillates.

FLAMMABLE: Keep away from ignition sources (heat, sparks or open flame). Ensure adequate ventilation to prevent build-up of vapours during application and drying.

NOTICE: Intentional mis-use by deliberately concentrating and inhaling contents may be harmful. **DO NOT TAKE INTERNALLY.** Avoid contact with eyes, skin and clothing. Can cause irritation.

First Aid

INHALATION: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

INGESTION: Do not induce vomiting. Get medical attention immediately

EYE CONTACT: Flush immediately with water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wash thoroughly with soap and water.



Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com | [facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

