



Product Description

A fast and easy way to add beautiful colour to unfinished wood. Tintable in hundreds of wood tones and contemporary decorative colours. Fast drying, low odour and easy clean-up with soap and water. For interior and exterior wood. Recommended for floors in combination with a sealer-topcoat such as **Woodtech Polyurethane Varnish** or **Berger Acrylic Over-Glaze**.

Surface Preparation

Surface must be clean, dry, smooth and free from dirt, grease and wax.

BARE WOOD: No primer or undercoats needed: can be used over Wood Preservative based coats. Surface oils must be removed with appropriate thinner.

STAINED WOOD: To freshen up previously stained wood with Woodtech Oil-Based Wood Stain, simply clean off any dirt and apply.

VARNISHED WOOD: Existing varnish should be stripped.

Application

Apply light coats with a clean brush or spray. Apply two coats on clean bare wood. If wood has been previously treated with **Woodtech Oil-Based Wood Stain**, re-apply one or two coats as needed. Remove any spilt stains immediately with **Berger No. 2 Reducer**. Can be overcoated with **Woodtech Polyurethane Gloss / Satin Varnish** or **Berger Acrylic Over-Glaze**.

Drying Time

After application, Woodtech Oil-Based Wood Stain will be 'touch dry' in 2 hours. The second coat, if necessary, can be applied after 4 hours.

Cleanup

Clean equipment immediately with Berger No. 2 Reducer. Store in a cool place.

Spreading Rate

16.5m² per litre on normal wooden surfaces. Two coats are recommended.

Flash Point

37°C (98°F)

Pack Sizes

3.8 litre, 0.95 litre

Colour Range

Woodtech Oil-Based Wood Stain is available in a range of colours. Ask your Berger Paints dealer to show you the Berger Oil-Based Wood Stain Colour Panels.



Health & Safety

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally. Liquid paint and vapours may cause irritation. Use only with adequate ventilation. To ensure fresh air entry, open all windows and doors. If headache or dizziness is experienced, use respiratory protection or leave area for fresh air. Avoid contact with skin or eyes.

First Aid

INGESTION: Do not induce vomiting. Get medical attention immediately.

INHALATION: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.

EYE CONTACT: Flush immediately with water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wash thoroughly with soap and water.



Contact Us



Berger Paints Barbados Ltd.
Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069
Tel: +1-246-425-9073
Fax: +1-246-228-0866
Email: info@bergeronline.com

Berger Paints Jamaica Ltd.
256 Spanish Town Road,
P.O. Box 8, Kingston 11, Jamaica
Tel: +1-876-923-6226
Fax: +1-876-923-5129
Email: bergerja_marketing@bergeronline.com

Berger Paints Trinidad Ltd.
P.O. Box 546, 11 Concessions Road,
Sea Lots, Port Of Spain, Trinidad
Tel: +1-868-623-2231
Fax: +1-868-623-1682

www.bergercaribbean.com | [facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.

